


VERSAFIT (2:1 RATIO)

Single Wall tube. A Premium grade heat shrink tube primarily used for electrical insulation. Has a UL224 approval and several Military related approvals. Available in several colours.



PRODUCT DIMENSIONS


SIZE	Inside Diameter as supplied (min) mm (inch) D	Inside Diameter after recovery (max) mm (inch) d	Wall Thickness after recovery (nom) mm (inch) W	Wall Thickness Tolerance after recovery mm (inch)
3/64	1.43 (0.056)	0.58 (0.023)	0.40 (0.016)	0.16 (0.006)
1/16	1.65 (0.066)	0.79 (0.031)	0.43 (0.017)	0.16 (0.006)
3/32	2.59 (0.103)	1.17 (0.046)	0.51 (0.020)	0.16 (0.006)
1/8	3.23 (0.128)	1.57 (0.062)	0.51 (0.020)	0.16 (0.006)
3/16	4.91 (0.193)	2.36 (0.093)	0.51 (0.020)	0.16 (0.006)
1/4	6.81 (0.268)	3.17 (0.125)	0.64 (0.025)	0.16 (0.006)
3/8	9.76 (0.384)	4.74 (0.187)	0.64 (0.025)	0.16 (0.006)
1/2	13.32 (0.524)	6.35 (0.250)	0.64 (0.025)	0.16 (0.006)
5/8	16.50 (0.650)	8.00 (0.315)	0.76 (0.030)	0.16 (0.006)
3/4	20.05 (0.790)	9.52 (0.375)	0.76 (0.030)	0.16 (0.006)
1	26.40 (1.040)	12.7 (0.500)	0.88 (0.035)	0.25 (0.010)
1-1/4	32.70 (1.290)	15.88 (0.625)	1.01 (0.040)	0.31 (0.012)
1-1/2	39.08 (1.540)	19.05 (0.750)	1.01 (0.040)	0.31 (0.012)
2	51.83 (2.040)	25.4 (1.000)	1.14 (0.045)	0.36 (0.014)
3	77.49 (3.050)	38.10 (1.500)	1.27 (0.050)	0.41 (0.016)
4	102.84 (4.100)	50.08 (2.000)	1.39 (0.055)	0.46 (0.018)

VERSAFIT (2:1 RATIO) – STANDARD SIZE REFERENCE DIMENSIONAL DRAWING



©2020 TE Connectivity Ltd. family of companies
All Rights Reserved

DIMENSIONS IN
mm (Inch)



SHEET

1 of 2

TITLE

**VERSAFIT (2:1 RATIO) – IRRADIATED
MODIFIED POLYOLEFIN SINGLE WALL
HEAT SHRINK TUBING**

NO

VERSAFIT (2:1 RATIO) – Standard Sizes

REV

A

REV

ENGINEERING CHANGE

CHK

DATE

VERSAFIT (2:1 RATIO)

PRODUCT INFORMATION

General use single wall Polyolefin Tubing.
Shrink Ratio – 2:1
Longitudinal Shrinkage on full recovery – 0 to -5%
Material conforms to TE Specification RW-3009
Standard Colours: Black, White, Red, Blue, Yellow
Non-Standard Colours: Brown, Orange, Green, Violet, Grey
Flame Retardant

Tubing cut to specific lengths can be supplied from the product sizes
referenced within this drawing.

Cut length tolerances are as per the following table:

STANDARD CUTTING TOLERANCES (mm)	
CUT LENGTH	TOLERANCE
Up to 9.9mm	±0.5mm
10mm to 24.9mm	±1.0mm
25mm to 54.9mm	±1.5mm
55mm to 99.9mm	±3.0mm
100mm to 149.9mm	±4.0mm
150mm to 499.9mm	±5.0mm
500mm to 1200mm	±12.5mm



TE Connectivity Ltd. family of companies

SHEET

2 of 2

NO.

**VERSAFIT (2:1 RATIO) –
Standard sizes**

REV

A